

KND312 / KND525

SNIPER RIFLE SCOPE

HIGH PERFORMANCE OPTICS
GRADUAL ILLUMINATED RETICLE
RETICLE FOCAL PLANE: 1





KND312 / KND525

SNIPER RIFLE SCOPE

Applications

- Sniper Rifle Scope

Main Features

- Continuous zoom
- Reticle focal plane: 1
- Gradual illuminated reticle

Standard Accessories

- Picatinny Adapter
- Protective Cover
- Transportation Case
- Cleaning Kit

Optional Accessories

- Reflex Sight
- Anti-reflection honeycomb filter

Environmental Conditions

- Operating Temperature : -30°C / +55°C
- Storage temperature : -40°C / +70°C
- Water Resistant : 1 m for 30 min.
- Environmental Spec : MIL-STD-810G

Technical Specifications	KND 312 3-12x50	KND 525 5-25x56
Magnification	3x-12x	5x-25x
Aperture	50 mm	56 mm
Field of View	11 m/ 3.4 m	5.3 m/1.5 m
Parallax Adjustment	From 50m to infinity	From 25m to infinity
Eye Relief	80 mm	85 mm
Wind./Ele. Adjustment	1 cm @ 100 m	
Total Reticle Movement	Windage :±60 clicks Elevation: 240 clicks	Windage :±60 clicks Elevation: 240 clicks
Double Turn Indicator	Yes	Yes
Reticle	Mil-Dot	Mil-Dot
Reticle Focal Plane	1st Focal Plane	
Reticle Illumination	11 Levels	
Diopter	-3/+2	
Battery	CR2032	
Weight	900 gr	1100 gr
Length	380 mm	430 mm